

Product Design

THERM-X IT-7270 is a 2 mil polyimide film tape with a silicone thermosetting pressure sensitive adhesive system.

Application

THERM-X IT-7270 was designed for use as a high performance insulation layer on coils and fractional horsepower motors. Excellent for bundling and protective outer wrap applications.

Performance Features

- ✓ Polyimide film backing offers **high conformability** and delivers **abrasion protection** and **puncture resistance** at high temperatures
- ✓ Performance silicone adhesive system is engineered for **high temperature performance** and **resists solvent contamination**
- ✓ **UL Listed** under file number E82910

Physical Properties	Value	Test Method
Backing Type	Polyimide film	
Backing Thickness	2 mils (0.05mm)	PSTC-33
Total Thickness	3.5 mils (0.09mm)	PSTC- 33
Adhesion to Steel	20 oz/in (5.5 N/25mm)	PSTC-101
Tensile Strength	65 lb/in (285 N/25mm)	PSTC- 31
Elongation %	60	PSTC-31
Adhesive System	Silicone	
Dielectric Strength	8,500 Volts	ASTM D-149-91
Insulation Class	180 C°	
Color	Amber	

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. 01/2016 Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants. CV-IT7270/0119

