

AutoWrap® 0130

PRODUCT DESIGN

AutoWrap GreenLeaf 0130 is a pressure sensitive, UV stabilized polyolefin film masking. The product is designed for the protection of textured exterior and interior finishes during assembly and transportation.

APPLICATION

AutoWrap GreenLeaf 0130 is used to protect textured exterior and interior parts including exterior mold in color plastics and interior parts plastic surfaces during shipment and storage. This product is not recommended for painted surfaces.

PERFORMANCE FEATURES

- Easy, one-piece removal leaves surfaces clean and stain-free
- Easily removable, even after extended periods of time
- Stays intact over bends and curved surfaces
- Adheres evenly to the applied surface
- Resists edge lift during transportation
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear/Blue
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@90°)	24 oz/in (6.7 N/25 mm)
Tensile Strength	11 lb/in (48 N/25 mm)
Elongation %	500
Backing	Polyolefin
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. NS-082925

