



Ideal Tape® 469, Cloth Duct Tape

PRODUCT DESIGN

Ideal Tape 469 is a standard grade polyethylene coated cloth tape with an aggressive rubber pressure sensitive adhesive, available in silver or black.

APPLICATION

Ideal Tape 469 is a general use duct tape suitable for a variety of applications. Common uses include general purpose packaging, bundling, and securing on the job site in abatement and weather proofing projects.

PERFORMANCE FEATURES

- Aggressive adhesive system performs on range of materials
- High conformability provides ease of use on rigid surfaces
- Tested in accordance with UL 723

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Tape Thickness	9 mils (0.23 mm)	PSTC-133
Peel Adhesion	40 oz/in (11 N/25 mm)	PSTC-101
Tensile Strength	18 lb/in (79 N/25 mm)	PSTC-131
Elongation	18%	
Temperature Resistance	32°F to 200°F (0°C to 93°C)	

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 18 months from the date of manufacture. Application surfaces should be clean, dry and free of grease, oil or other contaminants. NS 030923

Ideal Tape Co., Inc.

1400 Middlesex Street, Lowell, MA 01851

Toll Free: 800-229-9148 • WWW.IDEALTAPE.COM