



# ProtectRite® 7201

## PRODUCT DESIGN

ProtectRite 7201 is a 2 mil CoEx polyolefin film with a formulated acrylic pressure sensitive adhesive.

## APPLICATION

ProtectRite 7201 is generally used to protect mirror finish, polished #8 (28) mill finish, and bright annealed stainless steel. 7201 is also used to protect anodized aluminum, clear sealed aluminum, smooth acrylic, smooth polycarbonate, Formica, smooth HP laminates, vinyl coated metals, and painted metals.

## PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Conformable even during extreme bending
- Controlled unwind allows for easy application
- Can be supplied imprinted with your logo
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, Blue
Nominal Thickness	2 mils (0.05 mm)
Adhesion (@180°)	1.5 oz/in (0.41 N/25 mm)
Tensile Strength	7 lb/in (51 N/25 mm)
Elongation	600%
Backing	CoEx
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. RW-061424