



ProtectRite® 7252

PRODUCT DESIGN

ProtectRite 7252 is a 2 mil high clarity LDPE film specially designed to protect reflective surfaces. The custom formulated adhesive system offers virtually no adhesion build, even during extended application.

APPLICATION

ProtectRite 7252 is generally used to protect polyester coated aluminum, chrome, PVC and polycarbonate nameplate, acrylic panels, and metallized polyester.

PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Conformable even during extreme bending
- Controlled unwind allows for easy application
- Can be supplied imprinted with your logo
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	2 mils (0.05 mm)
Adhesion (@180°)	0.8 oz/in (0.22 N/25 mm)
Tensile Strength	7 lb/in (51 N/25 mm)
Elongation	550%
Backing	LDPE
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. RW-061424