ProtectRite® 7531

PRODUCT DESIGN

ProtectRite 7531 is a 5 mil low density polyethylene film with a formulated acrylic pressure sensitive adhesive.

APPLICATION

ProtectRite 7531 is generally used to permanently protect beverage printed polycarbonate, low pile carpets, and highly textures surfaces such as textured laminates, textures plastics/vinyl, painted "textured" steel/aluminum requiring a higher adhesion product during moderate fabricating and/or shipping.

PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Durable, resists scratching and abrasions
- Can be supplied imprinted with your logo
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	5 mils (0.13 mm)
Adhesion (@180°)	Ultra High
Tensile Strength	16 lb/in (70 N/25 mm)
Elongation	425%
Backing	LDPE
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. VB 060326

ProtectRite®

ABI Tape

105 Whittendale Drive, Moorestown, NJ 08057

Toll Free: 856-778-0708 • WWW.ABITAPE.COM