



ProtectRite® 8502

PRODUCT DESIGN

ProtectRite 8502 is a 2 mil smooth polypropylene film masking with a solvent rubber adhesive system. 8502 is designed for applications where die-cutting is typically utilized.

APPLICATION

ProtectRite 8502 is suggested for use on partially cured paints and coatings, lacquer-coated aluminum, die-cutting applications, and sublimation of trophy stock metal. 8502 is also used to protect appliance metals.

PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Specially designed adhesive system resists build, making for a uniform adhesion
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, Green
Nominal Thickness	2 mils (0.05 mm)
Adhesion (@90°)	11 oz/in (3.0 N/25 mm)
Tensile Strength	15 lb/in (66 N/25 mm)
Elongation	600%
Backing	Smooth Polypropylene
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. RW-061424