



ProtectRite® 8510

PRODUCT DESIGN

ProtectRite 8510 is a 3 mil high-performance polyolefin film designed for the protection of painted parts as well as coated and uncoated metals during fabrication. 8510 utilizes a specialty solvent rubber adhesive system offering excellent “quick-stick” properties and low adhesion build over long term application resulting in a clean easy removal. The high-performance polyolefin film backing offers excellent confirmability for metal fabrication including stamping, bending, and sheering. 8510 offers 6 months UV protection for outdoor applications.

APPLICATION

ProtectRite 8510 is a UV stable film designed to protect painted parts as well as both coated and uncoated metal during fabrication.

PERFORMANCE FEATURES

- Excellent Fabrication Properties
- UV Stable Protection for up to 6 months
- Specialty designed Solvent Rubber adhesive offers good initial “quick-stick” and low adhesion build over a variety of surfaces
- Solvent Rubber adhesive is non-reactive to freshly painted surfaces
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@90°)	11 oz/in (3.0 N/25 mm)
Tensile Strength	11 lb/in (48 N/25 mm)
Elongation	525%
Backing	Polyolefin
Printable Surface	No
Shelf Life	24 Months

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. RW 061424



ABI Tape

105 Whittendale Drive, Moorestown, NJ 08057

Toll Free: 856-778-0708 • WWW.ABITAPE.COM