



TransferRite Ultra® 592U

PRODUCT DESIGN

TransferRite Ultra 592U is a high grade saturated paper backing with superior adhesive technology designed for use over ready-to-apply graphics or where large areas of exposed liner are present. This product offers superior adhesion to liner.

APPLICATION

TransferRite Ultra 592U works well with printed and unprinted graphics and with pre-spaced lettering under 2" high. 592U can also be used for fine line striping and ready-to-apply graphics.

PERFORMANCE FEATURES

- Demonstrates superior adhesion to liner technology
- Lays flat to eliminate "dog-eared" decals
- Trouble-free stacking and storage of masked graphics
- Reduces wrinkling, tunneling, and edge lifting

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4.3 mils (0.11 mm)
Adhesion (@90°)	9 oz/in (2.5 N/25 mm)
Tensile Strength	21 lb/in (92 N/25 mm)
Elongation	2%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421