



# WheelMask® 0524

## PRODUCT DESIGN

WheelMask 0524 is a clear, UV Stable 4 mil product coated with a proprietary acrylic adhesive system. 0524 is available on a liner, for die-cut applications, or self-wound (without a liner).

## APPLICATION

WheelMask 0524 offers excellent blow-off resistance on the toughest wheel designs while allowing for a clean, stain-free removal in all temperatures. The self-wound version of 0524 allows both OEMs and Tiers to eliminate liner disposal time and cost. WheelMask 0524 works well with all painted OEM and alloy wheels.

## PERFORMANCE FEATURES

- Meets a variety of OEM specifications
- Resists blow-off adhering to the toughest wheel designs with minimal exposed area
- Available with or without liner
- Proprietary high performance acrylic adhesive system allows for clean, stain-free removal even after extended outdoor application in a wide range of environmental conditions

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	17 oz/in (4.7 N/25 mm)
Tensile Strength	35 lb/in (153 N/25 mm)
Elongation	690%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. NS 050423



ABI Tape

105 Whittendale Drive, Moorestown, NJ 08057  
Toll Free: 856-778-0708 • WWW.ABITAPE.COM