

TransferRite® Specialty Products

Multitasking

There's no end to what you can do with TransferRite®

Laser Mask - protects surfaces during engraving and color fill

- Eliminates smoke damage from laser beam heat
- Burns clean edges where color fill is required
- Removes cleanly and easily
- Available in medium and high tack

Pallet Mask - makes textile printing clean-up a breeze

- Reduce downtime for pallet clean-up
- Extend pallet life
- Eliminate need for costly solvents
- Eliminate hazardous and costly rag management

Paint Masks - two styles for a variety of applications

- StencilRite® - paintable paper-based removable substrate for temporary set design and displays
- StencilRite® - comes on a crepe liner for steel rule diecutting
- PM-50 is a matte yellow vinyl on a 78# liner, suitable for plotter cutting



Paint mask can be plotter cut for aluminum wayfinding signage, gym floors and vinyl coated backlit awning fabrics.



StencilRite® can also be used as a paintable substrate for set design and temporary displays.

TransferRite®

By  **ABI Tape**

Product Selection Guide: Specialty

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
Awards & Engraving				
582U	Medium	4	2%	Laser masking for smooth surfaces
592U	High	4	2%	Laser masking for textured surfaces
Textile				
PM-12	Medium	4	2%	Pallet mask for textile screen printing simplifies spray adhesive clean-up; Eliminates the need for cleaning solvents and hazardous rag disposal
Paint Mask				
PM-50	Medium	4		Vinyl paint mask for low temperature bake cycles <110°F; Resists urethanes and acrylic enamels; Removes cleanly
StencilRite 6932	High	8	6%	A heavy paper tape laminated to a crepe liner for steel rule die cutting; Excellent paint hold out; Also used as a substrate for set design and temporary displays

Applications recommendations - the performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American Biltrite Inc. assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products (unless otherwise noted) are not suitable for prolonged outdoor exposure.



105 Whittendale Drive • Moorestown, NJ 08057
 PH: (856) 778-0708 • FAX: (856) 778-7485
 Toll Free Fax: 888-224-6325 (US Only)

WWW.ABITAPE.COM