



Ideal Tape® 370, PVC Tape

PRODUCT DESIGN

Ideal Tape 370 is a self-wound white PVC tape with a pressure sensitive acrylic adhesive system.

APPLICATION

Ideal Tape 370 is designed for use indoors with pre-molded PVC insulation fittings. 370 is suitable for use to seal 45° and 90° joints, T's, long radius sweeps, and valves to pipe coverings.

PERFORMANCE FEATURES

- White PVC tape designed to match white pre-molded PVC insulation fitting
- High conformability allows for tight seal around irregular surfaces
- Self-wound tape is easy to use and requires no clean-up

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Tape Thickness	5 mils (0.13 mm)	ASTM D1000
Peel Adhesion	14 oz/in (4.0 N/25 mm)	ASTM D1000
Tensile Strength	10 lb/in (45 N/25 mm)	ASTM D1000
Elongation	100%	ASTM D1000
Application Temp. Range	-20°F to 250°F (-29°C to 121°C)	

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants. NS 031023

Ideal Tape Co., Inc.

1400 Middlesex Street, Lowell, MA 01851

Toll Free: 800-229-9148 • WWW.IDEALTAPE.COM