



AutoWrap® 0410

PRODUCT DESIGN

AutoWrap 0410 is a white, pressure sensitive, adhesive coated polyolefin film masking. The product is UV stabilized and designed to protect automotive finishes during transit to the dealer and for storage.

APPLICATION

AutoWrap 0410 protects automotive paint systems during shipment to dealer and in storage. 0410 provides antimutilation protection for painted automotive finishes, body, and bumper.

PERFORMANCE FEATURES

- Easy, one-piece removal leaves surfaces clean and stain-free
- Easily removable, even after extended periods of time
- Stays intact over bends and curved surfaces
- Adheres evenly to the applied surface
- Resists edge lift during transportation

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	14 oz/in (4.0 N/25 mm)
Tensile Strength	33 lb/in (144 N/25 mm)
Elongation %	700
Backing	Polyolefin
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-060321

ABI Tape



105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM