



# ProtectRite® 6560

## PRODUCT DESIGN

ProtectRite 6560 is a high grade, printable saturated fibrous paper backing with a specially formulated latex pressure sensitive adhesive system.

## APPLICATION

ProtectRite 6560 is designed to protect highly polished surfaces such as polished stainless steel, painted steel, chrome plated steel, and polished brass where a standard tack adhesive is required. 6560 is also used on mill finished and painted aluminum, specialty metals, synthetic marble, and glass. It is also used to protect aluminum aircraft skin during forming and processing, and it can be used on plastic laminates, acrylic, and polycarbonate sheeting.

## PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Specially designed adhesive system resists build, making for a uniform adhesion

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	3 oz/in (0.82 N/25 mm)
Tensile Strength	20 lb/in (88 N/25 mm)
Elongation	3%
Backing	Paper
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company - BSI Certificate #FM 26197. MK-070621