



# ProtectRite® 6782

## PRODUCT DESIGN

ProtectRite 6782 is a heavy duty masking with a specially formulated, low-build adhesive system.

## APPLICATION

ProtectRite 6782 is designed to protect various substrates such as acrylic and polycarbonate sheeting, stainless steel aluminum, and high pressure laminates.

## PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Withstands repeated silk screening cycles
- Heavy duty paper is extremely resistant to scratching and marring of protected surface

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	5 mils (0.13 mm)
Adhesion (@90°)	5 oz/in (1.4 N/25 mm)
Tensile Strength	21 lb/in (92 N/25 mm)
Elongation	14%
Backing	Paper
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-070621