



ProtectRite® 7333

PRODUCT DESIGN

ProtectRite 7333 is a 3 mil low density polyethylene film with a formulated acrylic pressure sensitive adhesive.

APPLICATION

ProtectRite 7333 is designed to protect residential and commercial carpets, painted textured surfaces, matte polycarbonates, and textured marble.

PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Easily unwound
- Puncture resistant
- Can be supplied imprinted with your logo

| PHYSICAL PROPERTIES | VALUE |
|---------------------|------------------------|
| Colors | Clear, White, Blue |
| Nominal Thickness | 3 mils (0.08 mm) |
| Adhesion (@180°) | 20 oz/in (5.4 N/25 mm) |
| Tensile Strength | 7.5 lb/in (33 N/25 mm) |
| Elongation | 325% |
| Backing | LDPE |
| Printable Surface | Yes |

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-072121