



ProtectRite® 7501

PRODUCT DESIGN

ProtectRite 7501 is a 25 mil low density polyolefin film with a formulated acrylic pressure sensitive adhesive.

APPLICATION

ProtectRite 7501 is generally used to protect highly polished stainless steel, bright annealed stainless steel, anodized stainless steel, smooth Formica, vinyl coated metals, painted metals, medium texture HP laminates, and clear sealed aluminum.

PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Conformable even during extreme bending
- Controlled unwind allows for easy application
- Can be supplied imprinted with your logo

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	5 mils (0.13 mm)
Adhesion (@180°)	1.5 oz/in (0.41 N/25 mm)
Tensile Strength	16 lb/in (70 N/25 mm)
Elongation	380%
Backing	LDPE
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-070621