



TransferRite® 6560

PRODUCT DESIGN

TransferRite 6560 is a low tack, high grade paper backing with a specially formulated latex pressure sensitive adhesive for general purpose use as pre-space and application tape.

APPLICATION

TransferRite 6560 is a low tack, pressure sensitive paper appropriate for general sign shop use and plastic protection during fabrication. It is an economical choice for large format vinyl installation. 6560 works well with one-piece decals measuring > 12" in one direction and pre-spaced computer cut lettering or logos > 12" high.

PERFORMANCE FEATURES

- Adheres to textured and smooth surfaces
- Clean release after installation
- Economically priced
- Lightweight, low tack

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	3 oz/in (0.82 N/25 mm)
Tensile Strength	25.4 lb/in (112 N/25 mm)
Elongation	2.4%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-072121

ABI Tape

TransferRite®

105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM