



TransferRite® 6592

PRODUCT DESIGN

TransferRite 6592 is a lightweight saturated paper backing coated with a specially formulated latex pressure sensitive adhesive system for general-purpose use as pre-space and application tape.

APPLICATION

TransferRite 6592 works well with intermediate vinyl films and pre-spaced lettering < 2" high. 6592 is used for fine line striping, smooth top-coated decals, thermal die-cuts, and 4 color process printing.

PERFORMANCE FEATURES

- High tack adhesive effectively picks up small graphics
- Translucent saturated paper backing enhances graphics' visibility
- Economical lightweight product construction

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4.2 mils (0.11 mm)
Adhesion (@90°)	10.5 oz/in (2.9 N/25 mm)
Tensile Strength	20 lb/in (88 N/25 mm)
Elongation	3%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421