



TransferRite® 6882

PRODUCT DESIGN

TransferRite 6882 is a heavyweight saturated paper backing coated with a unique, latex-based adhesive specifically designed for use over UV screen printed decals, especially 4 color process. 6882 provides excellent adhesion for transfer and installation, yet releases easily after use.

APPLICATION

TransferRite 6882 works well with one-piece decals, 4 color process printing, and digital prints.

PERFORMANCE FEATURES

- Rubber-based adhesive provides low adhesion and offers easy one-piece removal
- Heavyweight paper resists finger tunneling and lifting during shipping or extended storage periods
- Heavyweight paper allows for easy installation over rivets or corrugations

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	5.5 mils (0.14 mm)
Adhesion (@90°)	6 oz/in (1.6 N/25 mm)
Tensile Strength	21 lb/in (92 N/25 mm)
Elongation	13%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421

ABI Tape

TransferRite®

105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM