



TransferRite AirMask® 510U

PRODUCT DESIGN

TransferRite AirMask 510U is a unique clear polypropylene film backing with a custom formulated latex pressure sensitive adhesive for decal transfer and pre-spacing. 510U is a film premask with an affinity for air-release liners.

APPLICATION

TransferRite AirMask 510U is used with large format or cut graphics with exposed air-release liners.

PERFORMANCE FEATURES

- Effectively adheres to exposed air-release liners
- Works with a wide range of vinyl and liner brands
- Designed for cold lamination – no heat vacuum required
- Releases cleanly and easily upon installation

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	4.3 mils (0.11 mm)
Adhesion (@90°)	7 oz/in (1.9 N/25 mm)
Tensile Strength	24 lb/in (105 N/25 mm)
Elongation	570%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421

