



TransferRite Ultra® 1310

PRODUCT DESIGN

TransferRite Ultra 1310 boasts a unique rubber-based adhesive system that provides superior adhesion to liner. The 4 mil polypropylene film offers improved clarity, dimensional stability, and an adhesive system that will not haze vinyl.

APPLICATION

TransferRite Ultra 1310 works well with ready-to-apply graphics, banner material, and corrugated plastic. It also adheres well to decals or lettering < 12" in one dimension and multi-color overlays.

PERFORMANCE FEATURES

- Increased quick-stick resulting in effective part pick-up with intermediate films
- Heightened clarity with consistently accurate registration
- Ultra adhesive causes greater adhesion to liner, no tunneling, and no haze
- Dimensional stability and snap to tear stemming from polypropylene film

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	3.9 mils (0.10 mm)
Adhesion (@90°)	7 oz/in (1.9 N/25 mm)
Tensile Strength	15 lb/in (66 N/25 mm)
Elongation	665%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421