



TransferRite Ultra® 1320

PRODUCT DESIGN

TransferRite Ultra 1320 boasts a unique rubber-based adhesive system that provides superior adhesion to liner. The 4 mil polypropylene film offers improved clarity, dimensional stability, and an adhesive system that will not haze vinyl.

APPLICATION

TransferRite Ultra 1320 works well with pre-spaced lettering 2" - 12" high and one-piece decals. It also adheres well to mid-size line striping.

PERFORMANCE FEATURES

- High tack adhesive effectively picks up small graphics
- Heightened clarity with consistently accurate registration
- Ultra adhesive causes greater adhesion to liner, no tunneling, and no haze
- Dimensional stability and snap to tear stemming from polypropylene film

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	3.9 mils (0.10 mm)
Adhesion (@90°)	13 oz/in (3.6 N/25 mm)
Tensile Strength	15 lb/in (66 N/25 mm)
Elongation	665%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421

ABI Tape

TransferRite® ULTRA®

105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM