



ProtectRite® 8607

PRODUCT DESIGN

ProtectRite 8607 is a 3 mil Blue translucent film with a medium adhesion solvent natural rubber adhesive system.

APPLICATION

ProtectRite 8607 is designed for the protection of a broad range of substrates including painted and polished metals. Polyolefin film coupled with the solvent rubber adhesive system makes it an excellent choice for interior metal fabrication applications.

PERFORMANCE FEATURES

- SNR adhesive offers good “quick stick” to a variety of surfaces
- Excellent metal fabrication properties
- Low build adhesive
- Proudly manufactured in USA

PHYSICAL PROPERTIES	VALUE
Colors	Blue, Clear
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@180°)	7 oz/in (1.5 N/25 mm)
Tensile Strength	4 lb/in (18 N/25 mm)
Elongation	500%
Backing	PE
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. VB 032626