



## Ideal Tape® 427 PSK

### PRODUCT DESIGN

Ideal Tape 427 PSK has a white metallized PSK (Polypropylene/Scrim/Kraft) backing coated with an All Weather Formula (AWF) rubber based adhesive system on a paper release liner.

### APPLICATION

Ideal Tape 427 PSK is designed to seam, seal, and repair PSK insulation facings, including Lamtec® WMP-10 and WMP-30.

### PERFORMANCE FEATURES

- Meets ASTM C1136, Type II and IV
- All Weather Formula (AWF) adhesive system provides excellent bond and long term performance
- Release liner is easily removed for efficient application on the job site
- Tri-directional fiberglass/polyester reinforcement provides strength

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Tape Thickness	9.0 mils (0.23 mm)	PSTC-133
Peel Adhesion	80 oz/in (22 N/25 mm)	PSTC-101
Tensile Strength	40 lb/in (175 N/25 mm)	PSTC-131
Operating Temp. Range	-10°F to 180°F (-23.3°C to 82.2°C)	

### CLASSIFICATIONS

This product is 100% made in the USA of US-sourced components, making it compliant with Buy America and the Buy American Act

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 24 months from the date of manufacture. Application surfaces should be clean, dry and free of grease, oil or other contaminants. VB 012026

