



Ideal Tape® Cold Seal™ 728 ASJ

PRODUCT DESIGN

Cold Seal 728 ASJ is an All Service Jacket (ASJ) backing coated with a high performance cold weather acrylic adhesive system on a paper release liner.

APPLICATION

Cold Seal 728 ASJ is designed for sealing seams and joints of traditional ASJ faced fiberglass duct board. It is also a butt strip tape that matches the jacket in pipe covering fabrication.

PERFORMANCE FEATURES

- Meets ASTM C1136, Type I, II, III, and IV
- Performance acrylic adhesive system provides durable, long-term bond in extreme temperature conditions
- Release liner is easily removed for efficient application on the job site
- Tri-directional fiberglass reinforcement provides strength

| PHYSICAL PROPERTIES | VALUE | TEST METHOD |
|---------------------------------|---|--------------------|
| Tape Thickness | 9.0 mils (0.23 mm) | PSTC-133 |
| Peel Adhesion | 90 oz/in (25.0 N/25 mm) | PSTC-101 |
| Tensile Strength | 45 lb/in (197 N/25 mm) | PSTC-131 |
| Minimum Application Temp. | -5°F (-20°C) | |
| Operating Temp. Range | -35°F to 250°F (-37°C to 121°C) | |
| Surface Burning Characteristics | Flame Spread: ≤25 Smoke Developed: ≤50 | UL 723 ASTM E84 |

CLASSIFICATIONS

UL Classified, UL 723 Rated

This product is 100% made in the USA of US-sourced components, making it compliant with Buy America and the Buy American Act

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 24 months from the date of manufacture. Application surfaces should be clean, dry and free of grease, oil or other contaminants. VB 010926



ABI Tape®

105 Whittendale Drive, Moorestown, NJ 08057

Customer Service: (856) 778-0708 • WWW.IDEALTAPE.COM