



Ideal Tape® Cold Seal™ 729 ASJ+

PRODUCT DESIGN

Cold Seal 729 ASJ+ is made with a WMP® (White Metallized Polypropylene) ASJ backing, coated with a cold weather acrylic adhesive on a paper release liner.

APPLICATION

Cold Seal 729 ASJ+ is designed to seal seams and joints of WMP® ASJ fiberglass duct board. Also used as a butt strip tape that matches the jacket in pipe covering fabrication.

PERFORMANCE FEATURES

- Meets ASTM C1136, Type I, II, III, IV, X
- Performance acrylic adhesive system provides a durable, long-term bond in extreme temperature conditions
- Paper-free and mold resistant
- Matches Owens Corning and Knauf WMP® facings

PHYSICAL PROPERTIES	VALUE	TEST METHOD
Tape Thickness	10.0 mils (0.25 mm)	PSTC-133
Peel Adhesion	90 oz/in (25 N/25 mm)	PSTC-101
Tensile Strength	60 lb/in (263 N/25 mm)	PSTC-131
Minimum Application Temp.	-5°F (-20°C)	
Service Temp. Range	-35°F to 250°F (-37°C to 121°C)	
Surface Burning Characteristics	Flame Spread: ≤25 Smoke Developed: ≤50	UL 723 ASTM E84

CLASSIFICATIONS

UL Classified, UL 723 Rated

This product is 100% made in the USA of US-sourced components, making it compliant with Buy America and the Buy American Act

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 24 months from the date of manufacturing. Application surfaces should be clean, dry and free of grease, oil or other contaminants. VB 010926