



# ProtectRite® 7516

## PRODUCT DESIGN

ProtectRite 7516 is a 5 mil low density polyethylene film with a formulated acrylic pressure sensitive adhesive.

## APPLICATION

ProtectRite 7516 is used to protect HP laminates/textured, fabricating laminates/satin, and painted “textured” steel/aluminum.

## PERFORMANCE FEATURES

- Offers clean, stain-free removal
- Easily unwound
- Puncture resistant
- Can be supplied imprinted with your logo
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	5 mils (0.13 mm)
Adhesion (@180°)	High
Tensile Strength	16 lb/in (70 N/25 mm)
Elongation	380%
Backing	LDPE
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. VB 060326