



# ProtectRite® 8514

## PRODUCT DESIGN

ProtectRite 8514 is a 3 mil UV stable coextruded polyolefin film with a solvent rubber adhesive system.

## APPLICATION

ProtectRite 8514 works well on painted metal, including urethanes and coated plastics. 8514 also adheres well to partially cured paints and coatings.

## PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Specially designed adhesive system resists build, making for a uniform adhesion
- UV resistant up to 6 months
- Proudly made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Clear, Blue
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@90°)	14 oz/in (3.8 N/25 mm)
Tensile Strength	10 lb/in (44 N/25 mm)
Elongation	500%
Backing	CoEx Polyolefin
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. VB 021026