



LaserRite[®] *DUO* 8613

APPLICATION

LaserRite Duo 8613 is a high-performance material specially designed for the protection of polished metals during the laser cutting process.

- Designed to work with both Fiber and Co2 machines
- Recommended application temperature range between 100° and 120°F*
- Shelf Life is 12 months from date of manufacture
- UV Resistant up to 6 months

Time at temperate greatly impacts temperature range. ABI Tape recommends customers test in their process to confirm suitability in their application.

PERFORMANCE FEATURES

- Allows for the fastest cutting - No blow-up
- Excellent metal fabrication properties
- Proudly Union Made in USA

PHYSICAL PROPERTIES	VALUE
Colors	Gray/Black
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@180°)	13 oz/in (2.7 N/25 mm)
Tensile Strength	4 lb/in (18 N/25 mm)
Elongation	600%
Backing	Polyolefin
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company - BSI Certificate #FM 26197. VB 020526



LaserRite[®] *DUO*

ABI Tape
105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM